






9V28064 Flat - Vari-Twist® 9V280XX Series

			<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p>
---	---	--	--

Description:

Belden's PVC Vari-Twist series was designed to reduce crosstalk in the balanced mode by twisting the pairs, but can be mass-terminated in the flat sections with standard IDC connectors.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Pairs	32
Total Number of Conductors	64
AWG	28
Stranding	7x36
Conductor Material	TC - Tinned Copper

INSULATION:

Insulation Material	PVC - Polyvinyl Chloride
Nom. Insulation Wall Thickness	.010 in.
Insulation Resistance	>10, 000 Mega Ohms
Substrate Thickness and Material	.010" Clear PVC

PAIR:

Pair Lay Length & Direction - adjacent pairs	1/2" Nom. Lay Length - Adjacent pairs have opposite direction lay
--	---

Pair Color Code Chart :

Number	Color
1	Brown/Tan
2	Red/Tan
3	Orange/Tan
4	Yellow/Tan
5	Green/Tan
6	Blue/Tan
7	Purple/Tan
8	Gray/Tan
9	White/Tan
10	Black/Tan
Over 10 pair	Repeat as required

SPACING:



9V28064 Flat - Vari-Twist® 9V280XX Series

Conductor Spacing Center to Center Flat Section	.050 +/- .005 in.
Conductor Spacing Outside Center to Outside Center	3.15 +/- .020 in.
Twisted Pair Spacing Center to Center	.100 in.

OVERALL:

Overall Nominal Width	3.20 in.
Overall Nominal Thickness Flat Section	.042 +/- .003 in.
Overall Nominal Thickness Twisted Section	.080 in.
Overall Twisted Length	18 in.
Flat Section Center to Center Spacing	20 +/- .50 in.
Overall Flat Section Length	2 +.5/-0 in.

OUTER SHIELD:

Outer Shield Material	Unshielded
-----------------------	------------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-20°C To +105°C
-----------------------------	-----------------

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

UL AWM Style	2693 and 2697
UL Rating	105°C, 300 V RMS, VW-1
EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	10/01/2005

FLAME TEST:

UL Flame Test	VW-1
---------------	------

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

ELECTRICAL CHARACTERISTICS:

Nominal Balanced Characteristic Impedance :

Description	Nominal Balanced Characteristic Impedance (Ohms)
	115

Nominal Unbalanced Characteristic Impedance :

Description	Nominal Unbalanced Characteristic Impedance (Ohms)
	100

Nom. Inductance :

Description	Nominal Inductance (µH/ft)
@ 1 MHz	.24



9V28064 Flat - Vari-Twist® 9V280XX Series

Nom. Capacitance Conductor to Conductor :

Description	Nom. Capacitance Conductor to Conductor (pF/ft)
@ 1 kHz	20
@ 1 MHz	16

Nominal Velocity of Propagation :

Description	Nominal Velocity of Propagation (%)
	64

Nominal Delay 1.6 NS/FT. ns/ft

Nom. Conductor DC Resistance @ 20 Deg. C 68.2 OHMS/1000 FT. MAX. Ohms/1000 ft

Nom. Attenuation :

Description	Frequency (MHz)	Nom. Attenuation (dB/100 ft.)
	10	3.5
	20	5.5
	30	7.2
	40	8.8
	50	10.2
	60	12
	70	13
	80	14.2
	90	15
	100	16

Typical Balanced Crosstalk - dB Suppression :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Typ. dB Sup. for both near/far end is better than (dB)
10 ft. sample length		10	100	35

Typical Unbalanced Crosstalk :

Description	Pulse Rise Time (NS)	Near End (%)	Far End (%)	Typical Unbalanced Crosstalk (dB)
10 ft. sample length all grounds connected together.	3	5.8	5.2	
10 ft. sample length all grounds connected together.	5	4	3.2	
10 ft. sample length all grounds connected together.	7	2.5	2.8	

Max. Operating Voltage - UL 300 V RMS

Max. Recommended Current 1 Amp per conductor @ 20°C

Dielectric Withstand Voltage 2,000 V RMS

NOTES:

Notes The transition area is included in the twisted length to assure a full 2 inches of flat termination area.



9V28064 Flat - Vari-Twist® 9V280XX Series

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
9V28064 000H100	32 PR #28 PVC VARI-TWIST	H100	11.1	NONE	E

E = MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 25'

Revision Number: 1 Revision Date: 10-11-2005

© 2006 Belden Wire & Cable Company
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden CDT Electronics Division believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs.(San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003);Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden CDT Electronics Division declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.